


## 7. Door

Place door into position. Fix the two T-hinges to the door with 4 x 32mm screws per hinge. Secure the hinges to the front panel using 3 x 32mm screws per hinge. Attach the hasp and staple with 7 x 19mm round head screws. Fit the hasp to the door and the staple to the front panel ensuring that they are positioned so the hasp will fit over the staple.



## Important information

When positioning the shed, it is recommended that adequate provision is made to ensure ground contact is avoided and air is able to circulate underneath the building.

Placing the building on a concrete pad or slab base is acceptable provided that the building is not allowed to sit in pooled water during wet conditions. If the building is to sit on soil or grass it **MUST** be erected on pressure treated wooden 50mm x 50mm or similar bearers (**These are not supplied in the kit**).

Rowlinson Garden Products recommend using pressure treated bearers with all buildings on any type of base.

## Timber Information.

As timber is a natural material, there are certain weather conditions that may affect the materials properties. In times of excessive dry spells the material may lose some of its internal moisture causing a certain degree of shrinkage on a panel and in periods of excessive rain there will be a certain amount of swelling throughout the wooden panels. This process can not be avoided. If you have problems with certain boards shrinking in dry spells try to decrease the amount of direct sunlight on the building or the amount of air passing over the building. During hot spells spray water directly onto the panels with the aid of a garden hose.

If in doubt of any aspect regarding the assembly, use or safety of your building please contact us :

**Help Line (Normal Office Hours) 01829 261 121**

ROWLINSON GARDEN PRODUCTS LIMITED  
Green Lane  
Wardle Nr. Nantwich  
Cheshire  
CW5 6BN

We constantly improve the quality of our products, occasionally the components may differ from the components shown and are only correct at time of printing. We reserve the right to change the specification of our products without prior notice.

2011 © Rowlinson Garden Products Ltd

**ROWLINSON**  
GARDEN PRODUCTS

# 4x3 Oxford Shiplap Shed

# English SS276B

## Assembly Instructions

### Before assembly


- We recommend that time is taken to read the instructions before starting assembly, then follow the easy step by step guide. The instruction sheet is only a guide to the assembly. Certain items may not be shown to scale.
- Check all components prior to assembly
- This product should be assembled by no less than two people
- Drill all components where indicated



### Recommended tools for assembly


- Power drill/screwdriver
- 3mm drill bit
- Crosshead screwdriver bit
- Hammer
- Spirit level
- Sharp knife

**Biocidal Products Regulation EU 528/2012**  
PermaWood ACQ1900 treated wood is a treated article that incorporates biocidal products: copper hydroxide and Benzalkoniumchloride. They protect wood against fungal decay /rot/ and insect attack. Keep away from food, drink and animal feeding stuffs. Avoid breathing dust when cutting treated wood.




No.	Components	Qty.
1	Floor (1174 x 882mm)	1
2	Floor bearer (28 x 28 x 882mm)	4
3	Side panel	2
4	Back panel	1
5	Front panel	1
6	Roof purlin (45 x 28 x 882mm)	1
7	Roof panel (700 x 905mm)	2
8	Felt batten (28 x 28 x 905mm)	2
9	Roof felt (1.5m)	1
10	Bargeboard	4
11	Coverstrips (11 x 40 x 1580mm)	4
12	Door	1
13	Finials	2

No.	Fixing Kit	Qty.
14	T-hinge (200mm) (zinc)	2
15	Hasp and staple (zinc)	1
16	63mm screws	2
17	50mm screws	16
18	32mm screws	14
19	19mm round head screws	7
20	30mm nails	72
21	10mm felt nails	32



## 1. Floor section

Prepare a level area for the shed to sit. To the bottom of the floor, attach two floor bearers flush with the short edges of the floor using 4 x 30mm nails. Nail through the floor panel into the bearers. Attach the remaining two bearers spaced evenly between the first two in the same way.



### Important note

When positioning the shed, it is recommended that adequate provision is made to ensure ground contact is avoided and air is able to circulate underneath the building.

Placing the building on a concrete pad or slab base is acceptable provided that the building is not allowed to sit in pooled water during wet conditions.


If the building is to sit on soil or grass it **MUST** be erected on pressure treated wooden 50mm x 50mm or similar bearers (**These are not supplied in the kit**).

Rowlinson Garden Products recommend using pressure treated bearers with all buildings on any type of base.

## 2. Wall panels

Position the back panel and a side panel on the floor as shown. Note how the panel frames sit on the floor with the panel cladding overhanging the floor edge. Ensure square and secure using 3 x 50mm screws, screw through the frame of the side panel into the frame of the back panel. Attach the other side panel in the same way. Then add the front panel.

It is recommended to drill pilot holes for each screw before assembly.




## 3. Securing the walls to the floor

Ensure the panels are sitting square on the floor. Secure the front and rear panels using 2 x 50mm screws per panel, screw through the panel frames and floor into the centre floor joists. Secure the side panels from the outside using 2 x 30mm nails, nail through the panel cladding into the side of the floor.




It is recommended to drill pilot holes for each screw before assembly.



## 4. Roof Panels


Insert the roof purlin into the gap at the apex of the front and back panel framing, secure in place using 2 x 63mm screws. Secure a felt batten to each roof panel using 4 x 30mm nails as shown. Ensure the felt batten is flush to the edges of the panels. Position the roof panels onto the assembly, make sure the top edges are located at the apex and the roof is centred front and back to the body of the shed, secure the panels in place using 8 x 30mm nails per panel. Nail through the roof into the panel frames.

It is recommended to drill pilot holes for each screw before assembly.



## 5. Roof felt

Lay the roof felt centrally over the roof. On one side fold over the felt so it covers the felt batten and secure to the batten using 10 x 10mm felt nails. Tension the felt over the roof and fold the felt over the other felt batten and secure using 10 x 10mm to the batten. Dress the felt down over the front and back and secure each using 6 x 10mm felt nails. If necessary trim off any excess felt.



## 6. Coverstrips, bargeboards & finials

Fit a coverstrip into each corner, attach using 3 x 30mm nails per strip. To the front and rear of the shed, secure the bargeboards so that the top edge is flush with the roof line and the two boards meet evenly at the apex secure using 3 x 30mm nails per board. At the front and rear of the assembly, attach the finials at the apex over the joint between the bargeboards using 2 x 30mm nails per finial.

